



# ***ISR-1100 Stim-Series***

## Iron Sulfide Removal System

**ISR-1100 Series** is an anionic surfactant package that is low in pH and is designed to break iron sulfide down into small particulates, making for easier removal when acidizing or flowing back.

**ISR-1100 Series** has the capability of stripping any light hydrocarbon deposits that may coat the iron sulfide scale or formation face.

**ISR-1100 Series** delivers superior water wetting characteristics in both carbonate and sandstone reservoirs. The result is a more efficient stimulation, with residual wetting, that enhances the performance and life of an oil or gas well and its longevity.

**ISR-1100 Series** is excellent in the penetration and breaking of existing sludges created by previous stimulations.

**ISR-1100 Series** is an excellent carrier of fines and other insolubles, making it one of the best materials for the clean up of completion fluid and drilling fluid damage.

|                          |               |
|--------------------------|---------------|
| <b>Specific Gravity:</b> | 1.12          |
| <b>Appearance/Odor:</b>  | Amber/Vinegar |
| <b>Solubility:</b>       | Water         |
| <b>pH:</b>               | 1.0 to 1.5    |

**ISR-1100 Series** is recommended at a loading of 25 to 75 gallons per foot of desired treatment area. Volumes may change based on the severity of the damage and desired penetration in and into the formation. It is also suggested that samples be taken when possible as to ensure the most optimum performance and cost effectiveness.

*P.O. Box 2157  
Conroe, TX 77318  
[solutions@sosenvironmental.com](mailto:solutions@sosenvironmental.com)*